Exemplar-Controllable Paraphrasing and Translation using Bitext

Mingda Chen Sam Wiseman Kevin Gimpel
Toyota Technological Institute at Chicago, Chicago, IL, 60637, USA
{mchen, swiseman, kgimpel}@ttic.edu

Abstract

Most prior work on exemplar-based syntactically controlled paraphrase generation relies on automatically-constructed large-scale paraphrase datasets, which are costly to create. We sidestep this prerequisite by adapting models from prior work to be able to learn solely from bilingual text (bitext). Despite only using bitext for training, and in near zero-shot conditions, our single proposed model can perform four tasks: controlled paraphrase generation in both languages and controlled machine translation in both language directions. To evaluate these tasks quantitatively, we create three novel evaluation datasets. Our experimental results show that our models achieve competitive results on controlled paraphrase generation and strong performance on controlled machine translation. Analysis shows that our models learn to disentangle semantics and syntax in their latent representations, but still suffer from semantic drift. 1

1 Introduction

We consider the task of syntactically-controlled paraphrasing, which seeks to generate sentences that conform to desired syntax, specified either by syntactic templates (Iyyer et al., 2018) or a sentential exemplar (Chen et al., 2019a). Controlled paraphrasing can be used in collaborative and assistive writing technologies, which are deployed technologies used by creative writers (Manjavacas et al., 2017; Miller, 2019), English language learners (Chodorow et al., 2010; Abbas et al., 2020), students in educational settings (Weston-Sementelli et al., 2018), and marketing professionals (Huang and Rust, 2021). Writers use these tools to make their writing more fluent and professional, as well as to gain inspiration from seeing new ways to express their thoughts. Using sentential exemplars can provide a way to tailor the suggestions to match a desired syntactic pattern, without having to specify a linguistic structure such as a constituency tree. In the context of machine translation, controlled translation can be used to customize machine translation outputs in particular ways, such as producing simple sentence structures for ease of understanding. Also, controlled translation can be a way to produce multiple diverse translations which can be used for reranking or for presenting to users to provide a richer sense of the meaning of the original text when the 1-best translation is not useful (Mayhew et al., 2020).

Most prior work on controlled paraphrasing relies on large-scale paraphrase datasets, which are created automatically from bitext (Ganitkevitch et al., 2013; Wieting and Gimpel, 2018; Hu et al., 2019a). However, creating paraphrase datasets is costly (Wieting and Gimpel, 2018; Wieting et al., 2019a), so in this paper we focus on ways of learning to perform exemplar-based syntactically controlled paraphrasing and translation directly from bilingual text (bitext). Inspired by prior work on controlled paraphrase generation (Chen et al., 2019b,a), we use a deep generative sentence model with two latent variables for capturing syntax and semantics. Building on the assumption that the semantics of translation pairs are shared, but syntax varies, we adapt the multi-task objectives proposed by Chen et al. (2019b,a). The model only requires training on bitext, yet it is capable of exemplar-based syntactically controlled paraphrase generation and exemplar-based syntactically controlled machine translation in an almost zero-shot manner.

To evaluate models on these tasks quantitatively, we construct three datasets: one for Chinese controlled paraphrase generation, and the other two for Chinese-to-English and English-to-Chinese controlled machine translation. Similar to the dataset from Chen et al. (2019a), each instance in these datasets contains three items: a

¹Test data is available at https://github.com/mingdachen/mVGVAE.

semantic input, a syntactic exemplar, and a reference. Models must generate sentences that combine the semantics of the semantic input with the syntax of the syntactic input. When creating these datasets, we always first automatically construct a large pool of syntactic/semantic paraphrases and then perform heavy manual post-editing to ensure the quality of the dataset and difficulty of the tasks.

Empirically, for English controlled paraphrase generation, we show that (1) our models achieve competitive results compared to prior work that uses English paraphrase pairs and stronger results compared to prior work that uses translation pairs; (2) in order for the models trained on translation pairs to reach similar performance as those trained on paraphrase pairs, the translation-trained models need more training instances than the paraphrasetrained models. We also show that our models are able to perform Chinese controlled paraphrase generation and controlled machine translation without supervision for these tasks. Quantitative analysis shows that the models learn to disentangle semantics and syntax in latent representations. Qualitative analysis shows that our models suffer from semantic drift, especially for long sentences and in the controlled machine translation tasks, showing clear directions for future research.

2 Related Work

Paraphrase generation uses either monolingual parallel corpora (Quirk et al., 2004; Prakash et al., 2016; Gupta et al., 2018; Li et al., 2018) or bilingual parallel corpora by pivoting (Bannard and Callison-Burch, 2005; Ganitkevitch et al., 2013; Mallinson et al., 2017), back-translating (Wieting and Gimpel, 2018; Hu et al., 2019a,b), and more recently language modeling (Guo et al., 2019). Our focus in this work is syntactically-controlled paraphrasing and machine translation based on bitext, whereas most prior work on controlled paraphrase generation relies on English training data (Iyyer et al., 2018; Chen et al., 2019a; Goyal and Durrett, 2020; Kumar et al., 2020; Li et al., 2020; Kazemnejad et al., 2020).

Recently, Liu et al. (2020) show that machine translations can be used as training data for English syntactically-controlled paraphrasing. Relatedly, Wieting et al. (2019a) learn sentence embeddings directly from translations instead of paraphrase pairs, Wieting et al. (2019b) learn disentan-

gled sentence embeddings from translations, and Liu et al. (2019) learn syntactic sentence embeddings through translations and part-of-speech tags.

There is a long history of example-based machine translation (Nagao, 1984; Somers, 1999), and recently researchers find it helpful to build generations upon sentential exemplars (Guu et al., 2018; Weston et al., 2018). Our approach differs from prior work in that we use sentential exemplars for controllability instead of improving generation quality. Part of our evaluation involves syntactically controlled machine translation, relating it to syntax-based machine translation systems (Wu, 1997; Chiang, 2005; Sennrich and Haddow, 2016). Recently, Akoury et al. (2019) found it helpful in speeding up the decoding process.

3 Method and Evaluation

3.1 Method

To perform exemplar-based syntactically controlled generation from bitext, we follow an approach based on the vMF-Gaussian Variational Autoencoder (VGVAE) model (Chen et al., 2019b,a). VGVAE is a deep generative models with two latent variable models for modelling syntax and semantics, and it is trained with two multitask losses designed for monolingual paraphrase sentence pairs. To adapt VGVAE and the associated multi-task losses to multilingual settings, we make a few changes, including (1) the use of bytepair encoding (BPE; Sennrich et al., 2016); (2) we use language-specific syntactic encoders, but share the semantic encoder between the two languages; (3) we prepend a language-specific token to each input sentence. Details are in the appendix. We will call this model "mVGVAE".

The training of the mVGVAE only requires bitext, yet the trained model will contain necessary parameters to perform exemplar-based syntactically controlled paraphrase generation for either language. Moreover, training on bitext also makes the model suitable for cross-lingual tasks, such as exemplar-based syntactically controlled machine translation. In the following sections, we will demonstrate the model's ability to accomplish these tasks in an almost zero-shot fashion.

3.2 Controllable Paraphrase Generation with a Syntactic Exemplar

To evaluate the syntactic controllability of generation, Chen et al. (2019a) constructed a human-

```
X: his teammates' eyes got an ugly, hostile expression. Y: the smell of flowers was thick and sweet.
```

Z: the eyes of his teammates had turned ugly and hostile.

```
X: 只有团结一致,我们才能找到金子。
(only solidarity, we can find gold.)
Y: 你如果要帮我准备早餐,就要快点起床!
(you if want help me prepare breakfast, then quickly get up!)
Z: 我们如果想找到金子,就要团结起来!
(we if want find gold, then need solidarity!)
```

Figure 1: Top: an English example of exemplar-based syntactically controllable paraphrase generation from Chen et al. (2019a). Bottom: a Chinese example from our annotated dataset, where each sentence is followed by a gloss. Both examples have a semantic input X (red), a syntactic exemplar Y (blue), and a reference output Z (black).

annotated dataset in English. As shown in Figure 1, each instance in this dataset has three sentences: a semantic input, a syntactic input, and a reference output. The semantic input shares similar semantics to the reference, but they have different syntax. The syntactic input shares similar syntax to the reference, but they have different semantics. Solving this task requires models to be able to disentangle the syntax and semantics of the input sentences and manipulate these representations to generate the desired output.

Training on bitext allows our models to perform generation in languages other than English. To evaluate this capability, we construct a similar dataset in Chinese, as shown in Figure 1. Since there is no large-scale Chinese paraphrase dataset available, we first automatically tag the Chinese sentences obtained from the Chinese-English OpenSubtitles corpus (Lison and Tiedemann, 2016), and then for each sentence, we find a sentence that shares the most similar syntax in the same corpus by computing the edit distance between the part-of-speech tag sequences. ter obtaining these syntactic paraphrases, a native Chinese speaker paraphrases the references, following the data construction process described in Chen et al. (2019a) to ensure syntactic mismatch between the semantic input and the syntactic input, and semantic mismatch between the syntactic input and the reference. This contributes 378 instances. We also consider using Chinese instances that are translated from our English controlled paraphrase generation test set, and then we ask the annotator to heavily post edit these instances to ensure the criteria mentioned earlier are met. The final dataset contains 800 instances.

```
W: 鹰钩鼻和僵硬的颧骨使他的脸看起来很奇怪 (hawk-bridged nose and stiff cheekbones let his face look very strange.) Y: clarke was a short man with bushy black brows and brown eyes.
```

Z: he had a strangely shaped face with a hawk-bridged nose and stiff cheekbones.

W: the failure of your students is the failure of yours. Y: 杰克的不负责任和布莱恩的信誓旦旦真的是天作之合。

(jack's irresponsibility and bryan's promises really are perfect match .) Z: 你学生的失败和你的失败是一回事。

(you student's failure and your failure are the same thing .)

Figure 2: Top: an example in our Chinese-to-English syntactically controlled translation dataset. Bottom: an example in our English-to-Chinese syntactically controlled translation dataset. Both examples have semantic input W (violet), syntactic exemplar Y (blue), and reference output Z (black). Each Chinese sentence is followed by a gloss.

When performing syntactically controlled generation, we first use the syntactic exemplar $x_{\rm syn}$ as the input to the syntactic encoder to obtain the syntactic representation (mean of the Gaussian distribution), then we combine it with the semantic representation (mean direction of the vMF distribution) obtained from the semantic input $x_{\rm sem}$ and feed them to the decoder for generation.

For this task, we report BLEU (Papineni et al., 2002) and syntactic tree edit distance (ST) scores. For ST, we follow Chen et al. (2019a) to first parse the generated sentence and the reference with the Stanford CoreNLP toolkit (Manning et al., 2014) and then compute the tree edit distance between these two parse trees. Lower ST is better. Since the ST scores between the generations and references are similar to the ones between the generations and syntactic inputs, we choose to report the former for simplicity and include the latter in the supplementary material. For other metrics, including ROUGE (Lin, 2004) and METEOR (Banerjee and Lavie, 2005), please refer to the supplementary material.

3.3 Controllable Machine Translation with a Syntactic Exemplar

Motivated by the fact that our models are trained on bitext, we create a novel task, where the semantic input is from the source language, and the syntactic input and reference are from the target language. Examples for both English-to-Chinese and Chinese-to-English tuples are shown in Figure 2. Compared to the task of generating paraphrases, this task is more challenging in that it requires translation and syntactic control simultaneously.

We construct evaluation datasets based on the monolingual syntactically-controlled paraphrase datasets described in the previous section. We first use Google Translate to translate the semantic inputs, and then manually go through these sentences to ensure that (1) there is no grammatical error or semantic drift in the translations; and (2) there is strong syntactic mismatch between the translations and the references, so that the task can not be trivially solved by translating the semantic inputs.

When evaluating models on these two datasets, we mostly follow the process used for paraphrase generation except that we use the language-specific syntactic encoders to encode the syntactic inputs. We report BLEU and ST scores for this task.

4 Experiments

4.1 Training

The training of our models uses bitext from Open-Subtitles.² We report results on Chinese-English (Zh-En) sentence pairs. Results on German-English (De-En), Spanish-English (Es-En), and French-English (Fr-En) sentence pairs are in the supplementary material. As baselines, we train models on Czech-English (Cs-En) sentence pairs from the CzEng corpus (Bojar et al., 2016) and English-English (En-En) sentence pairs from the ParaNMT-50M dataset (Wieting and Gimpel, 2018), which is constructed by back-translating the CzEng corpus.

For all these datasets, we first tokenize text with the Stanford CoreNLP toolkit and then use BPE with 30,000 merge operations. Chen et al. (2019a) used several heuristics for additional filtering of the 5-million-pair preprocessed subset of ParaNMT-50M released by Wieting and Gimpel (2018), eventually using half a million paraphrase pairs for training. As these heuristics are not directly applicable to bitext, we use the full 5million preprocessed subset for En-En. For Zh-En, we randomly sample 5 million sentence pairs. To make the results more comparable to prior work on English controllable paraphrasing, for both settings and the CzEng corpus, we also report results that use 0.5 million sentence pairs, randomly sampled. We use word noising during training (Chen et al., 2019a), and the probability of noising a word is 90%. We perform early stopping based on

the BLEU score from the development set. More details, such as runtime and hyperparameters, are in the appendix.

We only have a development set for the English paraphrase generation task, for which we use the dev split from Chen et al. (2019a). For the other tasks, we do not have development sets. We treat our newly-created datasets (described in Sections 3.2 and 3.3) as test sets and report results on them. Therefore, we can consider our results on these tasks to be zero-shot or zero-shot crosslingual results.

4.2 Results

Controlled Paraphrase Generation. For English and Chinese paraphrase generation, we report two groups of baselines. The first group is "return-input", where we return either the syntactic input or the semantic input as the prediction. As shown in Tables 1 and 2, compared to the semantic input, the syntactic input leads to better ST score but worse semantic-related scores, i.e., BLEU.³ This reflects our consideration about the differences between these two when constructing the dataset.

For English paraphrasing, the second group of baselines is models trained on ParaNMT. The empirical comparison to prior work (Chen et al., 2019a) shows the impact of several changes made when modifying mVGVAE for use with bitext, such as BPE, as well as the difference in training data filtering. Our model (En-En) achieves worse performance in semantic-related metrics compared to prior work when training on the same amount of data. Using more data partially mitigates the performance gap.

For models trained on bitext, our model obtains stronger performance than Liu et al. (2020) when training on the same amount of data. However, the results for our models and Liu et al. (2020) are not strictly comparable as their models are trained on different datasets. The difference between the results for 0.5M En-En and 0.5M Cs-En shows the advantage of learning from monolingual paraphrase pairs as compared to bitext. Compared to training on 0.5M Cs-En, we are able to obtain slightly better performance when training on 0.5M Zh-En sentence pairs.⁴ We also find that after in-

²http://www.opensubtitles.org/

³When evaluating Chinese sentences, the metrics are computed at the character-level, following the process described in Ma et al. (2019).

⁴We also experimented with other language pairs in order

	%BLEU (↑)	ST (↓)	
Return-input base	lines		
Syntactic input	3.3	5.9	
Semantic input	18.5	12.0	
Models trained on the Para	NMT dataset		
Chen et al. (2019a) (0.5M En-En)	13.6	6.7	
0.5M En-En	11.7	6.8	
5M En-En	13.0	6.6	
Models trained on bitext			
Liu et al. (2020) (0.5M Zh-En)	8.7	9.8	
0.5M Cs-En	9.3	7.6	
0.5M Zh-En	9.9	7.2	
5M Zh-En	11.5	6.7	
5M Zh-En Big	12.5	6.7	

Table 1: English controlled paraphrase generation.

creasing the amount of training data to 5M, we are able to match the performance of the 0.5M En-En model. Prior work on learning sentence representations from bitext (Wieting et al., 2019a) also found that training on bitext requires more data than training on English paraphrase data. In light of the strong performance, we will report results that use 5M sentence pairs for the following experiments.

Although models trained on 5M Zh-En bitext perform worse on English paraphrase generation in terms of the BLEU score, they show strong performance on the ST score, suggesting that these generations share similar syntax with the syntactic inputs but they are not faithful to the semantic inputs (e.g., in Sec. 5.4, we find that the model suffers from semantic drift). It is also worth noting that (1) compared to the model trained on ParaNMT, the model trained on Zh-En only trains on half the number of English sentences; (2) during training, the models never get to train on paired monolingual sentences, yet they manage to control the syntax in the generations.

Nonetheless, to offer a competitive baseline for future work, we train a large model with 1000 hidden units per direction on 5 million instances of Zh-En bitext, and report the results as "Zh-En Big" in the tables. As shown in Tables 1 and 2, increasing model size boosts performance significantly.

Controlled Machine Translation. As we do not have semantic inputs in the same language as references in this setting, the "return-input" baseline for the semantic input would score very badly. So, we evaluate standard machine translation systems on these tasks as baselines, simply applying them

	%BLEU (↑)	ST (↓)	
Return-i	Return-input baselines		
Syntactic input	6.2	13.9	
Semantic input	49.0	18.7	
Our work			
Zh-En	12.8	15.8	
Zh-En Big	16.6	15.5	

Table 2: Chinese controlled paraphrase generation.

	%BLEU (↑)	ST (↓)
Return-ir	put baselines	
Syntactic input	3.3	5.9
Neural machine translation baselines		
OpenNMT	11.0	11.5
Google Translate	14.5	11.6
Our work		
Zh-En	10.9	6.7
Zh-En Big	12.1	6.6

Table 3: Chinese→English controlled translation.

to the semantic input and ignoring the syntactic input. The systems we consider include (1) a neural sequence-to-sequence model trained on the same 5 million Zh-En bitext using OpenNMT (Klein et al., 2017)⁵; and (2) Google Translate.

Test results are shown in Tables 3 and 4. We note that to obtain the OpenNMT results in these two tables, we need to train two separate models on two directions of the Zh-En bitext, whereas we can use a single mVGVAE model for both translation directions (in addition to both paraphrasing tasks). The two tables show that these machine translation systems achieve strong performance on the semantic metric (BLEU), but weak performance on the syntactic metric (ST). This highlights that success of syntactic controllability of generation depends on using the syntactic inputs. Our large model achieves the best results in ST in these two tables and still manages to obtain reasonable BLEU scores.

5 Analysis

5.1 Human Evaluation

We conduct a human evaluation to verify the extent to which the syntax of generations matches the syntax of the syntactic inputs. We use Amazon Mechanical Turk and ask human annotators to give scores ranging from 1 to 5 (with 1 being the most dissimilar) for the syntactic similarity between the generated output and the syntactic inputs (details are in the supplementary mate-

to study the relationship between performance and language choice but did not observe any clear patterns. More details are in the supplementary material.

⁵We use a 2-layer bidirectional LSTM on the encoder and a 2-layer unidirectional LSTM on the decoder. Both LSTMs have 500 hidden units per direction.

	%BLEU (↑)	ST (↓)
Return-ir	put baselines	
Syntactic input	6.2	13.9
Neural machine translation baselines		
OpenNMT	12.3	19.2
Google Translate	30.3	18.5
Our work		
Zh-En	9.6	16.1
Zh-En Big	11.9	15.7

Table 4: English→Chinese controlled translation.

	English test set		
	sem.	syn.	Δ
Prior work (En-En)	74.3	7.4	66.9
Our work (En-En)	74.9	12.0	62.9
Our work (Zh-En)	73.6	16.3	57.3
	Chinese test set		
fastText	74.0		
Our work	76.2	23.5	52.8

Table 5: Pearson's correlation (%) for the semantic similarity tasks.

rial). We collect 79 annotations (1 annotation per instance) for each of three systems. Similar to what we observe with the ST metric, our model performs the best on the average score among the three systems (Table 8). These results provide validation that our ST metric captures syntactic similarity as measured by human judges.

5.2 Disentanglement of Latent Representations

To evaluate the extent of disentanglement of the syntactic and semantic representations, we follow the idea of Chen et al. (2019b) and test our trained models on both semantic and syntactic similarity tasks. When computing sentence representations, we first use the inference model $q_{\phi}(y|x)$ or $q_{\phi}(z|x)$ and then we either use the mean direction of vMF distribution or the mean of Gaussian distribution to obtain the semantic or syntactic representations for sentences. We expect that compared to the syntactic latent representations, the semantic ones would perform better on semantic tasks and worse on syntactic tasks, and vice versa. The performance gap between the two representations can be used as an indicator for the disentanglement of syntactic variables and semantic variables.

For the semantic evaluation of English sentences, we use the test set from the sentence textual similarity (STS) benchmark (Cer et al., 2017). For Chinese, we use the 1360 human-annotated instances from Wang et al. (2017). These datasets provide human annotations for pairs of sentences, indicating the semantic similarity of the given sentences.

	POS	S Accur	acy	CP I	Labeled	F_1
	sem.	syn.	Δ	sem.	syn.	Δ
]	English	test set	;	
Oracle		62.3			71.1	
Random		12.9			19.2	
PW (En-En)	20.3	43.7	23.4	24.8	40.9	16.1
En-En	19.6	44.9	25.3	24.2	42.4	18.2
Zh-En	19.7	44.4	24.7	24.4	41.7	17.3
		(Chinese	test se	t	
Oracle		56.6			58.2	
Random	13.4			17.8		
fastText		18.7			21.7	
Zh-En	15.0	36.2	21.2	19.3	32.3	12.9

Table 6: POS tagging accuracy (%) and constituent parsing labeled F_1 scores (%) for the syntactic evaluation. PW = prior work.

tence pair. We report the Pearson correlation between the human annotation and the cosine similarity computed based on the sentence representations.

For the syntactic evaluation, we follow the procedure described by Chen et al. (2019b) to automatically parse and tag sentences using the Stanford CoreNLP toolkit for all languages except English. For English, we use the existing dataset provided by Chen et al. (2019b). Then, we randomly pick 300 sentences for each length (up to 30) as test sets, and leave the rest of the sentences with the same length as candidates. We use the sentence representations to retrieve the nearest neighbor in the candidate pool for sentences in the test set, and compute the distance metrics between these two sentences by computing labeled F_1 scores for constituency parse (CP) trees or accuracies for part-of-speech (POS) tagging. The syntactic match between the nearest neighbors and the query sentences can illustrate the extent of syntactic information that the sentence representations have captured. This kind of retrieval-based approach has been shown to be effective in sequence labeling (Wiseman and Stratos, 2019).

Semantic Evaluation. We report results for the English semantic similarity task in Table 5. We report the best model from Chen et al. (2019a) as "Prior work". For the Chinese test set, we also benchmark fastText (Bojanowski et al., 2017) on it by using the averaged word vectors as the sentence representation. In comparing to prior work, our En-En model performs worse on the Δ value, and performs better on the semantic variable.

In general, as suggested by the large Δ values, our models learn to disentangle the semantic information in the syntactic variable and semantic variable

Query Sentence	Semantically Similar	Syntactically Similar
with a gun, you feel more dangerous.	i 'll give him a gun if it makes you feel	all these days, i could n't work, i could
i would n't know .	any better.	n't sleep.
你从窗户外可以看到它或在电视上 也会看到它	你几乎不可能再近距离看到它的, 用望远镜也不行	我在国会上讲过我们需要建桥但我 们会靠自己
(you from window outside can see it	(you almost no possible again close	(i at congress talked we need build a
or in tv also can see it)	distance see it, use telescope also not	bridge but we can depend on ourselves)
	work)	

Table 7: The most similar sentences to particular query sentences in terms of the semantic variable and syntactic variable based on the model trained on Zh-En bitext. Each Chinese sentence is followed by a gloss. More examples are in the supplementary material.

	Avg.	Std.
OpenNMT	2.4	1.2
Google Translate	2.4	1.1
Our model (Zh-En Big)	3.5	1.4

Table 8: Human evaluation results for Chinese-to-English controlled machine translation. We report the average and standard deviation of scores that measures the syntactic similarity between the generations and the syntactic inputs. Higher is better for the average scores.

able, offering results competitive with prior work. This shows that training on bitext yields similar disentanglement as training on paraphrases. This phenomena also generalizes to other languages, as shown in Table 5, where we report results for the Chinese semantic similarity task (see the supplementary material for more results on other languages). Although the semantic variable outperforms fastText by around 2 points, the syntactic variable has a much lower result, leading to a Δ value similar to the English test set. It is worth noting that when computing semantic representations, there is no language-specific parameter aside from special language tokens that are prepended to the input sequences, yet the models still manage to learn to encode semantic information for different languages.

Syntactic Evaluation. We report results for the English syntactic evaluation and the Chinese syntactic evaluation in Table 6. We also report two baseline results for the datasets. One is "Oracle", where we use the parse trees or POS tags to search for nearest neighbors. This can serve as upper bound performance of the task. The other one is "Random", where we randomly select sentences as our predictions, and we report results averaged over ten runs. This can serve as a lower bound performance of the task. For the Chinese test set, we also report a fastText baseline based on the averaged word vectors.

Similar to what we observe in the semantic sim-

ilarity tasks, our models can disentangle syntactic information in the latent variables, either in the English dataset or the datasets in other languages (see supplementary materials for more results on other languages). On the Chinese test set, fast-Text is slightly better than the semantic variable of our model, whereas the syntactic variable achieves much better performance.

5.3 Nearest Neighbors

We analyze nearest neighbors based on cosine similarities between query sentences drawn from the test sets and candidates with the same length from the syntactic evaluation candidate set. Table 7 shows the nearest neighbors found by either the semantic variable or the syntactic variable. Similar to Chen et al. (2019a), who trained on paraphrases, models trained on bitext also capture different characteristics for different latent variables. The semantically similar sentences share similar topics with the query sentences, while their syntactic structures are very different. The syntactically similar sentences have similar syntax to the query sentences, while their topics are different. For example, "with a gun ... wouldn't know." and "i'll give him ... any better" both talk about guns, whereas "all these days ... couldn't sleep" is about working and sleeping, which is topically unrelated to the previous two sentences. However, the syntactic variable still gives it the highest similarity due to the similar syntactic structure. Similar effects can be observed for the Chinese nearest neighbors.

5.4 Generation Samples

In Table 9, we compare generation examples from the "En-En" model to those from the "Zh-En Big" model. Both models are trained on 5 million sentence pairs. In general, we find the models are able to generate sentences that exhibit the expected syntax without changing the semantics. However, for

Semantic Input	Syntactic Input	En-En Model	Zh-En Big Model
this 's a crime, you know	they understand that was a	you know that was a crime	you know this was a crime?
that , right ?	chance ?	?	
how exciting that is .	that 's exactly right.	that 's so exciting.	that 's so exciting.
the mayor will be called	when this report is found, it	when the government is in-	when the mayor gets hurt,
for responsibility by citi-	will give us ideas on the fu-	formed, they will call it the	they will call you a lot of cit-
zens when these policies	ture of the factory.	citizens of the responsibility	izens for a while.
fail .		of policy.	
by his side crouched a huge	a giant yellow bird lives on	the black fish wolf catches	a fish black market is beside
black wolfish dog .	it.	behind him.	him .

Table 9: Example outputs from the "En-En" and "Zh-En Big" models for the English controlled paraphrase generation tasks. Both models are trained on 5 million sentence pairs.

Semantic Input	Syntactic Input	Generation		
Chinese Controlled Paraphrase Generation				
我厌倦了你的深夜探访。(i tired of	他们的耽搁使他发疯了。(their de-	你的访客让我厌烦了。(your visitor		
your late night vists.)	lay made him crazy .)	made me tired .)		
Engli	sh-to-Chinese Controlled Machine Tra	nslation		
They succeeded because they found	因为它呈现了最下乘的科学,所	因为他们发现了最成功的节奏,因为		
the same rhythm	以我们不应该使用它。(because it			
	shows the worst science, so we should	the most successful thythm, because		
	not use it .)	they all found it .)		
Chin	Chinese-to-English Controlled Machine Translation			
我不能成为一名吸毒者或酗酒者?	why ca n't it eat dried peas or some-	why could n't i have been drinking or		
为什么? (i can not become a drug ad-	thing ?	something?		
dict or an alcoholic ? why ?)				

Table 10: Example outputs from the "Zh-En Big" model for our three new controlled generation tasks. Each Chinese sentence is followed by a gloss. More examples are in the supplementary material.

long inputs, the outputs from the Zh-En model become more noisy in terms of semantic preservation. For example, see the third instance in the table, where the En-En output is a bit garbled but still uses topically-relevant phrases (e.g., "responsibility of policy") whereas the Zh-En output has changed the semantics dramatically ("the mayor gets hurt"). In addition, we find that the subword tokenization may have a negative impact on the model performance. In the last example in the table, although the semantic and the syntactic inputs never talk about fish, the outputs from both models contain the word "fish", which is likely due to the fact that the "wolfish" in the semantic input is tokenized into "wol@@ fish" by the byte pair encoding where "@@" is the separator between non-final subword units.

In Table 10, we demonstrate generation examples from the Zh-En Big model for the other three tasks considered in this paper. In general, the model tends to give higher priority to the syntactic input than the semantic input, even at the cost of faithfulness to the semantic input. For example, in Chinese controlled paraphrase generation, the semantic input "i tired of your late night visits" gets transformed into "your visitor made me tired.", which shows strong syntactic similarity to the syn-

tactic input, although the word "visit" is replaced by the word "visitor". This sort of semantic drift occurs more often in controlled machine translation. For example, in English-to-Chinese translation, the instance with similar semantic and syntactic input is translated into "your visitor made me late", which mistranslates both "visit" and "tired", although the syntax of the instance remains very similar to that of the syntactic input.

However, it is worth noting that the model manages to transform function words into appropriate words that fit the context. For example, in Chinese-to-English controlled machine translation, the phrase "why can't it eat" is transformed into "why couldn't i have been". It is also interesting to see that the model only needs to be trained once on Zh-En bitext to perform all four of these tasks.

6 Conclusion

We tailored a disentanglement method so that it can be trained on bitext instead of paraphrases, and demonstrated that it can learn to perform exemplarbased syntactically controlled paraphrasing and machine translation in an almost zero-shot fashion. We annotated three new datasets targeting these tasks which will be made available. Quantitative analysis shows that our model learns to disentangle semantics and syntax in the latent representations, though it still suffers from semantic drift when performing controlled generation, suggesting directions for future work.

References

- Muhammad Azeem Abbas, Shiza Hammad, Gwo-Jen Hwang, Sharifullah Khan, and Syed Mushhad Mustuzhar Gilani. 2020. An assistive environment for EAL academic writing using formulaic sequences classification. *Interactive Learning Environments*, pages 1–15.
- Eneko Agirre, Carmen Banea, Claire Cardie, Daniel Cer, Mona Diab, Aitor Gonzalez-Agirre, Weiwei Guo, Rada Mihalcea, German Rigau, and Janyce Wiebe. 2014. SemEval-2014 task 10: Multilingual semantic textual similarity. In *Proceedings of the 8th International Workshop on Semantic Evaluation (SemEval 2014)*, pages 81–91, Dublin, Ireland. Association for Computational Linguistics.
- Nader Akoury, Kalpesh Krishna, and Mohit Iyyer. 2019. Syntactically supervised transformers for faster neural machine translation. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 1269–1281, Florence, Italy. Association for Computational Linguistics.
- Satanjeev Banerjee and Alon Lavie. 2005. METEOR: An automatic metric for MT evaluation with improved correlation with human judgments. In *Proceedings of the ACL Workshop on Intrinsic and Extrinsic Evaluation Measures for Machine Translation and/or Summarization*, pages 65–72, Ann Arbor, Michigan. Association for Computational Linguistics.
- Colin Bannard and Chris Callison-Burch. 2005. Paraphrasing with bilingual parallel corpora. In *Proceedings of the 43rd Annual Meeting of the Association for Computational Linguistics (ACL'05)*, pages 597–604, Ann Arbor, Michigan. Association for Computational Linguistics.
- Piotr Bojanowski, Edouard Grave, Armand Joulin, and Tomas Mikolov. 2017. Enriching word vectors with subword information. *Transactions of the Association for Computational Linguistics*, 5:135–146.
- Ondřej Bojar, Ondřej Dušek, Tom Kocmi, Jindřich Libovický, Michal Novák, Martin Popel, Roman Sudarikov, and Dušan Variš. 2016. CzEng 1.6: Enlarged Czech-English Parallel Corpus with Processing Tools Dockered. In *Text, Speech, and Dialogue: 19th International Conference, TSD 2016*, number 9924 in Lecture Notes in Computer Science, pages 231–238, Cham / Heidelberg / New York / Dordrecht / London. Masaryk University, Springer International Publishing.

- Daniel Cer, Mona Diab, Eneko Agirre, Iñigo Lopez-Gazpio, and Lucia Specia. 2017. SemEval-2017 task 1: Semantic textual similarity multilingual and crosslingual focused evaluation. In *Proceedings of the 11th International Workshop on Semantic Evaluation (SemEval-2017)*, pages 1–14, Vancouver, Canada. Association for Computational Linguistics.
- Mingda Chen, Qingming Tang, Sam Wiseman, and Kevin Gimpel. 2019a. Controllable paraphrase generation with a syntactic exemplar. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 5972–5984, Florence, Italy. Association for Computational Linguistics.
- Mingda Chen, Qingming Tang, Sam Wiseman, and Kevin Gimpel. 2019b. A multi-task approach for disentangling syntax and semantics in sentence representations. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 2453–2464, Minneapolis, Minnesota. Association for Computational Linguistics.
- David Chiang. 2005. A hierarchical phrase-based model for statistical machine translation. In *Proceedings of the 43rd Annual Meeting of the Association for Computational Linguistics (ACL'05)*, pages 263–270, Ann Arbor, Michigan. Association for Computational Linguistics.
- Martin Chodorow, Michael Gamon, and Joel Tetreault. 2010. The utility of article and preposition error correction systems for english language learners: Feedback and assessment. *Language Testing*, 27(3):419–436
- Juri Ganitkevitch, Benjamin Van Durme, and Chris Callison-Burch. 2013. PPDB: The paraphrase database. In *Proceedings of the 2013 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 758–764, Atlanta, Georgia. Association for Computational Linguistics.
- Tanya Goyal and Greg Durrett. 2020. Neural syntactic preordering for controlled paraphrase generation. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*. Association for Computational Linguistics.
- Yinpeng Guo, Yi Liao, Xin Jiang, Qing Zhang, Yibo Zhang, and Qun Liu. 2019. Zero-shot paraphrase generation with multilingual language models. *arXiv preprint arXiv:1911.03597*.
- Ankush Gupta, Arvind Agarwal, Prawaan Singh, and Piyush Rai. 2018. A deep generative framework for paraphrase generation. In *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence, (AAAI-18), the 30th innovative Applications of Artificial Intelligence (IAAI-18), and the 8th AAAI Symposium on Educational Advances in Artificial Intelligence (EAAI-18), New Orleans, Louisiana, USA, February 2-7, 2018*, pages 5149–5156. AAAI Press.

- Kelvin Guu, Tatsunori B. Hashimoto, Yonatan Oren, and Percy Liang. 2018. Generating sentences by editing prototypes. *Transactions of the Association for Computational Linguistics*, 6:437–450.
- Sepp Hochreiter and Jürgen Schmidhuber. 1997. Long short-term memory. *Neural computation*, 9(8):1735–1780.
- J. Edward Hu, Rachel Rudinger, Matt Post, and Benjamin Van Durme. 2019a. ParaBank: Monolingual bitext generation and sentential paraphrasing via lexically-constrained neural machine translation. In *Proceedings of AAAI*.
- J. Edward Hu, Abhinav Singh, Nils Holzenberger, Matt Post, and Benjamin Van Durme. 2019b. Large-scale, diverse, paraphrastic bitexts via sampling and clustering. In *Proceedings of the 23rd Confer*ence on Computational Natural Language Learning (CoNLL), pages 44–54, Hong Kong, China. Association for Computational Linguistics.
- Ming-Hui Huang and Roland T. Rust. 2021. A strategic framework for artificial intelligence in marketing. *Journal of the Academy of Marketing Science*, 49:30–50.
- Mohit Iyyer, John Wieting, Kevin Gimpel, and Luke Zettlemoyer. 2018. Adversarial example generation with syntactically controlled paraphrase networks. In Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers), pages 1875–1885, New Orleans, Louisiana. Association for Computational Linguistics.
- Amirhossein Kazemnejad, Mohammadreza Salehi, and Mahdieh Soleymani Baghshah. 2020. Paraphrase generation by learning how to edit from samples. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 6010–6021, Online. Association for Computational Linguistics.
- Guillaume Klein, Yoon Kim, Yuntian Deng, Jean Senellart, and Alexander Rush. 2017. OpenNMT: Opensource toolkit for neural machine translation. In *Proceedings of ACL 2017, System Demonstrations*, pages 67–72, Vancouver, Canada. Association for Computational Linguistics.
- Ashutosh Kumar, Kabir Ahuja, Raghuram Vadapalli, and Partha Pratim Talukdar. 2020. Syntax-guided controlled generation of paraphrases. *ArXiv*, abs/2005.08417.
- Yinghao Li, Rui Feng, Isaac Rehg, and Chao Zhang. 2020. Transformer-based neural text generation with syntactic guidance. *arXiv preprint arXiv:2010.01737*.
- Zichao Li, Xin Jiang, Lifeng Shang, and Hang Li. 2018. Paraphrase generation with deep reinforcement learning. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language*

- *Processing*, pages 3865–3878, Brussels, Belgium. Association for Computational Linguistics.
- Chin-Yew Lin. 2004. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pages 74–81, Barcelona, Spain. Association for Computational Linguistics.
- Pierre Lison and Jörg Tiedemann. 2016. OpenSubtitles2016: Extracting large parallel corpora from movie and TV subtitles. In *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC 2016)*, pages 923–929, Portorož, Slovenia. European Language Resources Association (ELRA).
- Chen Liu, Anderson De Andrade, and Muhammad Osama. 2019. Exploring multilingual syntactic sentence representations. In *Proceedings of the 5th Workshop on Noisy User-generated Text (W-NUT 2019)*, pages 153–159, Hong Kong, China. Association for Computational Linguistics.
- Mingtong Liu, Erguang Yang, Deyi Xiong, Yujie Zhang, Chen Sheng, Changjian Hu, Jinan Xu, and Yufeng Chen. 2020. Exploring bilingual parallel corpora for syntactically controllable paraphrase generation. In *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence, IJCAI-20*, pages 3955–3961. International Joint Conferences on Artificial Intelligence Organization. Main track.
- Qingsong Ma, Johnny Wei, Ondřej Bojar, and Yvette Graham. 2019. Results of the WMT19 metrics shared task: Segment-level and strong MT systems pose big challenges. In *Proceedings of the Fourth Conference on Machine Translation (Volume 2: Shared Task Papers, Day 1)*, pages 62–90, Florence, Italy. Association for Computational Linguistics.
- Jonathan Mallinson, Rico Sennrich, and Mirella Lapata. 2017. Paraphrasing revisited with neural machine translation. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 1, Long Papers*, pages 881–893, Valencia, Spain. Association for Computational Linguistics.
- Enrique Manjavacas, Folgert Karsdorp, Ben Burtenshaw, and Mike Kestemont. 2017. Synthetic literature: Writing science fiction in a co-creative process. In *Proceedings of the Workshop on Computational Creativity in Natural Language Generation (CC-NLG 2017)*, pages 29–37, Santiago de Compostela, Spain. Association for Computational Linguistics.
- Christopher Manning, Mihai Surdeanu, John Bauer, Jenny Finkel, Steven Bethard, and David McClosky. 2014. The Stanford CoreNLP natural language processing toolkit. In *Proceedings of 52nd Annual*

- Meeting of the Association for Computational Linguistics: System Demonstrations, pages 55–60, Baltimore, Maryland. Association for Computational Linguistics.
- Stephen Mayhew, Klinton Bicknell, Chris Brust, Bill McDowell, Will Monroe, and Burr Settles. 2020. Simultaneous translation and paraphrase for language education. In *Proceedings of the Fourth Workshop on Neural Generation and Translation*, pages 232–243, Online. Association for Computational Linguistics.
- A.I. Miller. 2019. The Artist in the Machine: The World of AI-Powered Creativity. MIT Press.
- Makoto Nagao. 1984. A framework of a mechanical translation between japanese and english by analogy principle. In *Proc. of the international NATO symposium on Artificial and human intelligence*, pages 173–180.
- Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of* the 40th Annual Meeting of the Association for Computational Linguistics, pages 311–318, Philadelphia, Pennsylvania, USA. Association for Computational Linguistics.
- Aaditya Prakash, Sadid A. Hasan, Kathy Lee, Vivek Datla, Ashequl Qadir, Joey Liu, and Oladimeji Farri. 2016. Neural paraphrase generation with stacked residual LSTM networks. In *Proceedings of COLING 2016*, the 26th International Conference on Computational Linguistics: Technical Papers, pages 2923–2934, Osaka, Japan. The COLING 2016 Organizing Committee.
- Chris Quirk, Chris Brockett, and William Dolan. 2004. Monolingual machine translation for paraphrase generation. In *Proceedings of the 2004 Conference on Empirical Methods in Natural Language Processing*, pages 142–149, Barcelona, Spain. Association for Computational Linguistics.
- Rico Sennrich and Barry Haddow. 2016. Linguistic input features improve neural machine translation. In *Proceedings of the First Conference on Machine Translation: Volume 1, Research Papers*, pages 83–91, Berlin, Germany. Association for Computational Linguistics.
- Rico Sennrich, Barry Haddow, and Alexandra Birch. 2016. Neural machine translation of rare words with subword units. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1715–1725, Berlin, Germany. Association for Computational Linguistics.
- Harold Somers. 1999. Example-based machine translation. *Machine translation*, 14(2):113–157.

- Shaonan Wang, Jiajun Zhang, and Chengqing Zong. 2017. Exploiting word internal structures for generic Chinese sentence representation. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pages 298–303, Copenhagen, Denmark. Association for Computational Linguistics.
- Jason Weston, Emily Dinan, and Alexander Miller. 2018. Retrieve and refine: Improved sequence generation models for dialogue. In *Proceedings of the 2018 EMNLP Workshop SCAI: The 2nd International Workshop on Search-Oriented Conversational AI*, pages 87–92, Brussels, Belgium. Association for Computational Linguistics.
- Jennifer L. Weston-Sementelli, Laura K. Allen, and Danielle S. McNamara. 2018. Comprehension and writing strategy training improves performance on content-specific source-based writing tasks. *International Journal of Artificial Intelligence in Education*, 28:106–137.
- John Wieting and Kevin Gimpel. 2018. ParaN-MT-50M: Pushing the limits of paraphrastic sentence embeddings with millions of machine translations. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 451–462, Melbourne, Australia. Association for Computational Linguistics.
- John Wieting, Kevin Gimpel, Graham Neubig, and Taylor Berg-Kirkpatrick. 2019a. Simple and effective paraphrastic similarity from parallel translations. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4602–4608, Florence, Italy. Association for Computational Linguistics.
- John Wieting, Graham Neubig, and Taylor Berg-Kirkpatrick. 2019b. A bilingual generative transformer for semantic sentence embedding. ArXiv, abs/1911.03895.
- Sam Wiseman and Karl Stratos. 2019. Label-agnostic sequence labeling by copying nearest neighbors. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 5363–5369, Florence, Italy. Association for Computational Linguistics.
- Dekai Wu. 1997. Stochastic inversion transduction grammars and bilingual parsing of parallel corpora. *Computational Linguistics*, 23(3):377–403.

A Details of Methods

We begin by briefly reviewing the learning objective and parameterization of mVGVAE, and then describe the changes we make to adapt it to the multilingual setting. For more details, please refer to the original papers.

Learning Objectives. mVGVAE is a neural latent-variable sentence model with two latent variables, one for modeling semantics (denoted by y and drawn from a von Mises-Fisher prior) and one for syntax (denoted by z and drawn from a Gaussian prior).

mVGVAE assumes sentences x are generated by independent latent variables y and z, leading to a factorized joint probability $p_{\theta}(x,y,z) = p_{\theta}(y)p_{\theta}(z)p_{\theta}(x\,|\,y,z)$. Furthermore, mVGVAE assumes a factorized approximated posterior $q_{\phi}(y,z|x) = q_{\phi}(y|x)q_{\phi}(z|x)$. Combining these two assumptions gives rise to one of the learning of objectives of mVGVAE, the ELBO:

$$\log p_{\theta}(x) \ge \underset{\substack{y \sim q_{\phi}(y|x) \\ z \sim q_{\phi}(z|x)}}{\mathbb{E}} [\log p_{\theta}(x|z,y)]$$

$$- KL(q_{\phi}(z|x)||p_{\theta}(z)) - KL(q_{\phi}(y|x)||p_{\theta}(y))$$
(1)

Similar to Chen et al. (2019a), we associate weights with the KL terms. In our experiments, we use $1e^{-3}$ for z and $1e^{-4}$ for y. To adapt VG-VAE to bitext, we use subword units, i.e., byte-pair encoding (BPE; Sennrich et al., 2016), instead of whole word tokenization.

In addition to Eq. (1), Chen et al. (2019a) introduced other losses for multi-task training: a paraphrase reconstruction loss (PRL) and a word position loss (WPL). We directly apply these two losses to our bitext setting. In particular, PRL for a parallel sentence pair (x_1,x_2) takes the form

$$\mathbb{E}_{\substack{y_{2} \sim q_{\phi}(y|x_{2}) \\ z_{1} \sim q_{\phi}(z|x_{1})}} [\log p_{\theta}(x_{1}|y_{2}, z_{1})] + \\ \mathbb{E}_{\substack{y_{1} \sim q_{\phi}(y|x_{1}) \\ z_{2} \sim q_{\phi}(z|x_{2})}} [\log p_{\theta}(x_{2}|y_{1}, z_{2})]$$
(2)

That is, instead of reconstructing a sentence from its syntactic variable and the semantic variable of its paraphrase, we reconstruct a sentence from its syntactic variable and the semantic variable of its *translation*.

The WPL loss adds a classifier to explicitly predict word position at each time step t using the concatenation of subword unit embedding e_t and the syntactic variable z produced by the approximated posterior. Formally, WPL is defined as follows:

$$\mathbb{E}_{z \sim q_{\phi}(z|x)} \left[\sum_{t} \log \operatorname{softmax}(f([e_{t}; z]))_{w_{t}} \right]$$

where f is a 3-layer feedforward neural network, softmax $(\cdot)_i$ indicates the probability at position i,

and w_t is the word boundary at t, i.e., the position in x of the original word that contains the t-th subword unit. Though we use BPE encoding, we define the ground truth positions for WPL using the original word boundaries. Unlike Chen et al. (2019a), we find the latent code does not help model performance when using subword units, so we do not include it in our models.

Finally, the learning objective for mVGVAE is

$$ELBO + PRL + WPL$$
 (3)

Parameterization. Similar to Chen et al. (2019a), we parameterize the syntactic encoder $q_{\phi}(z|x)$ with a bidirectional long short-term memory (LSTM; Hochreiter and Schmidhuber, 1997) network, and the semantic encoder $q_{\phi}(y|x)$ with a word averaging module. Each is then followed by a 2-layer feedforward neural network for encoding the mean direction of the vMF distribution or the mean and the variance of the Gaussian distribution. The $p_{\theta}(x|z,y)$ is parameterized with a unidirectional LSTM.

We also allocate language-specific parameters to better model bitext. To indicate the languages of the input sentences, we prepend a language-specific token to each input sentence. Additionally, we use language-specific syntactic encoders, but share the semantic encoder between the two languages as we assume that the semantics between sentence pairs are shared. The syntactic and semantic encoders do not share subword unit embeddings.

The training of the mVGVAE only requires bitext, yet the trained model will contain necessary parameters to perform exemplar-based syntactically controlled paraphrase generation for either language. Moreover, training on bitext also makes the model suitable for cross-lingual tasks, such as exemplar-based syntactically controlled machine translation. In the following sections, we will demonstrate the model's ability to accomplish these tasks in an almost zero-shot fashion.

B Hyperparameter and Model Size

We follow the hyperparameters used in Chen et al. (2019a) and did not perform any other hyperparameter search for fair comparison. We use 50 as the latent dimension for most of the models, except for the big model, where we use 100. Similarly, we use beam size 10 when evaluating models on test sets.

Our big model has 220.5 million parameters, and the other mVGVAE models each has 30.5 million parameters. OpenNMT baseline has 47.4 million parameters.

C Generation Samples

We show generation examples in Table 11.

D Nearest Neighbors

We show the nearest neighbour examples in Table 12.

E Runtime and Computing Infrastructures

Our models are trained on machines equipped with a single GPU, such as NVIDIA TITAN X or NVIDIA 2080 Ti. We train all of our models for 20 epochs. For the big model, it takes approximately 11.67 hours to finish one epoch. For other mVGVAE models, it takes 6.67 hours to finish one epoch.

F Human Evaluation

During human evaluations, annotators were asked one question: "On a scale of 1-5, how much do you think the structure of sentence1 and the structure of sentence2 are similar?", and we show the detailed explanation for each option in Table 13.

G Controlled Paraphrase Generation

We report BLEU, ROUGE-1, ROUGE-2, ROUGE-L, and METEOR. For ST metrics, we report ST-r and ST-s, which are computed between the generations and references, and the generations and syntactic inputs respectively.

We report English controlled paraphrase generation results in Table 14. It is interesting to see that models trained on other language pairs can also lean to perform this task.

We report results for Chinese controlled paraphrase generation in Table 15, Chinese-to-English controlled machine translation in Table 16, and English-to-Chinese controlled machine translation in Table 17. ⁶

H Semantic Disentanglement

We report results for semantic evaluation for other languages in Table 18 and Table 19. For Spanish,

we use the Spanish test set from STS 2017 (Agirre et al., 2014). We found that models trained on other language pairs also learn to disentangle latent representations.

I Syntactic Disentanglement

We report results for syntactic evaluation for other languages in Table 20 and Table 21. We found that models trained on other language pairs also learn to disentangle latent representations.

⁶When computing ROUGE scores for Chinese, we map Chinese characters to unique IDs to avoid encoding problems.

Semantic Input	Syntactic Input	Generation	
Chinese Controlled Paraphrase Generation			
我厌倦了你的深夜探访。(i tired of	他们的耽搁使他发疯了。(their de-	你的访客让我厌烦了。(your visitor	
your late night vists.)	lay made him crazy .)	made me tired .)	
我认为,如果她愿意选择这个坟	如果那是他们想要的,你们为什么	如果她是我们选择的,她就不会结	
■ 墓,我们没有理由将她嫁给一个	要这样玩呢? (if that is they want,	婚了。(if she is we choose, she will	
贵族。(i think, if she willing choose	you why like this play ?)	not marry .)	
this grave, we no reason will she			
marry a noble)			
帮助我们学习是布拉德的目的(help	瑞德是去坑害那些百姓的。(reed is	布拉德是想帮助我们学习的。(brad	
us learn is brad's purpose)	going entrap those common people .)	is want help us learn .)	
	glish Controlled Paraphrased Generat		
no demonic force can harm you while	as soon as i start the escape sequence,	as long as you 're a little devil, no one	
this blade is at your hip.	an alarm will sound .	will hurt .	
why are n't his motives written down	why not take a look at your verdict?	why not write the letter of his motive	
?		?	
no more drugs for him!	do n't watch it all day!	do n't give him any drugs!	
	h-to-Chinese Controlled Machine Tran		
Unless nothing happened to him, why	如果是笑着说话,人是能听出来	如果是想知道原因,事情会是不会	
would n't we know?	的。(if is smile talk, other people can	发生的? (if is want to know the rea-	
	hear it .)	son, the thing is not going to happen	
		?)	
I 'm tired of your late night visits.	他们的耽搁使他发疯了。(their de-	你的访客让我迟到了(your visitor	
	lay made him crazy .)	made me late .)	
They succeeded because they found	因为它呈现了最下乘的科学,所	因为他们发现了最成功的节奏,因	
the same rhythm	以我们不应该使用它。(because it	为他们都找到了它。(because they	
	shows the worst science, so we should	found the most successful thythm, be-	
	not use it .)	cause they all found it .)	
	se-to-English Controlled Machine Tran		
你知道你已经是个死人吗? (you	do you need them stopped immedi-	do you know you were dead?	
know you already is a dead man ?)	ately ?		
我不能成为一名吸毒者或酗酒者?	why ca n't it eat dried peas or some-	why could n't i have been drinking or	
为什么? (i can not become a drug ad-	thing ?	something ?	
dict or an alcoholic ? why ?)			
给史密斯先生买些面包。(give mr.	let 's take a look at the mechanism.	let 's get some money for a drink.	
smith buy some bread .)			

Table 11: Example outputs for our four controlled generation tasks. Each Chinese sentence is followed by a gloss.

Query Sentence	Semantically Similar	Syntactically Similar
with a gun, you feel more dangerous.	i 'll give him a gun if it makes you feel	all these days, i could n't work, i could
i would n't know.	any better.	n't sleep.
if you want the loo, it 's just out here	the bathroom 's at the end of the corri-	when you need a car, you pull it right
in the corridor.	dor, if you need it.	out of the tree .
it 's bumpy, but we 'll be past it in a	it 's gon na be a little bumpy till we	it looks negligible, but it will be diffi-
few minutes .	get over the mountains.	cult to get any useful samples.
"who are you to talk to me like that?	talk to me, just tell me who you are.	what 're you gon na do to me with that
		?
十五步之远我们的客厅是屋子里最	这间客房是更大的,我需要多一点	如今整个银河中你们的星球是文明
大的房间	空间。	程度最低的星球
(fifteen step away our living room be	(this guest room be bigger, I need	(now entire Galaxy in you of planet be
house inside the biggest room)	more a little space .)	civilization degree the most low planet)
你从窗户外可以看到它或在电视上	你几乎不可能再近距离看到它的,	我在国会上讲过我们需要建桥但我
也会看到它	用望远镜也不行	们会靠自己
(you from window outside can see it	(you almost no possible again close	(i at congress talked we need build a
or in tv also can see it)	distance see it, use telescope also not	bridge but we can depend on ourselves)
	work)	
我们完全有能力为我们的女儿举办	我们糊弄他们,我们将会举行一个	我们很可能会为我们的驻罗分公司
一个独特的婚礼	很大的婚礼	选一些管理层的人士
(we absolutely have capability for our	(we fool them, we will host a very big	(we very possible can for our zhuoluo
daughter hold a unique wedding)	wedding)	branch select some management per-
		son)
看它的胸腔在动他正在呼吸大量氧	Foreman 做了胸腔穿刺术来排出她	闯进她的公寓拿着刀你已经越线太
气	肺部的积水	远了
(look its chest cavity be move he being	(Forema did chest cavity puncture to	(break into she apartment hold knife
breathe great amount oxygen)	discharge she lungs stagnant water)	you already cross the line too far)

Table 12: The most similar sentences to particular query sentences in terms of the semantic variable and syntactic variable based on the model trained on Zh-En bitext. Each Chinese sentence is followed by a gloss. More examples are in the supplementary material.

- 1 = The two sentences are completely dissimilar in structure.
- 2 = The two sentences do not have very similar structure overall, but there are some similarities (e.g., both start with an independent clause that begins with a subject, or both contain a dependent clause introduced by "that").
- 3 = The two sentences are roughly equivalent in overall structure, but individual clauses in the sentences have different structures.
- 4 = The two sentences have similar structure overall, but there are some small differences (e.g., one sentence has more modifiers (adjectives or adverbs) than the other).
- 5 = The two sentences are completely equivalent, as they have the same sentence structure.

Table 13: Detailed explanation for each option for human evaluations.

	BLEU	ROUGE-1	ROUGE-2	ROUGE-L	METEOR	ST-r	ST-s				
Return-input baselines											
Syntactic input	3.3	24.4	7.5	29.1	12.1	5.9	0.0				
Semantic input	18.5	50.6	23.2	47.7	28.8	12.0	13.0				
	1	Models trained	l on the ParaN	MT dataset							
Prior work (En-En)	13.6	44.7	21.0	48.3	24.8	6.7	3.4				
En-En	13.0	44.0	20.0	47.4	23.6	6.6	3.3				
		Models train	ed on bitext (our work)							
Cs-En	12.1	41.5	18.0	45.1	22.4	6.9	3.4				
Zh-En	11.5	42.7	18.3	46.1	22.2	6.7	3.4				
Zh-En Big	12.5	44.6	18.7	47.4	23.2	6.7	3.5				
De-En	12.6	42.1	18.4	45.8	22.1	6.6	3.2				
Es-En	11.7	41.3	17.5	44.9	21.8	6.8	3.7				
Fr-En	11.3	41.1	17.6	44.6	21.2	6.7	3.3				

Table 14: Test set results for English controlled paraphrase generation. The models are trained on 5 million sentence pairs. Lower is better for ST-r and ST-s.

	DIEII	DOLLCE 1	DOLLCE 3	DOLLCE I	METEOD	CT	CT -			
	BLEU	ROUGE-1	ROUGE-2	ROUGE-L	METEOR	ST-r	ST-s			
Return-input baselines										
Syntactic input	6.2	29.9	9.2	34.4	13.2	13.9	0.0			
Semantic input	49.0	77.4	57.0	65.4	42.5	18.7	22.4			
	Our work									
Zh-En	12.8	46.1	20.6	46.4	21.2	15.8	12.6			
Zh-En Big	16.6	52.4	26.0	50.8	24.8	15.5	12.0			

Table 15: Test set results for the Chinese controlled paraphrase generation. Lower is better for ST-r and ST-s.

	BLEU	ROUGE-1	ROUGE-2	ROUGE-L	METEOR	ST-r	ST-s					
	Return-input baselines											
Syntactic input	3.3	24.4	7.5	29.1	12.2	5.9	0.0					
	Neural machine translation baselines											
OpenNMT	11.0	42.4	17.0	43.1	23.4	11.5	12.0					
Google Translate	14.5	47.7	20.8	46.5	27.3	11.6	12.6					
Our work												
Zh-En	10.9	40.6	17.9	44.2	21.3	6.7	3.3					
Zh-En Big	12.1	42.2	18.3	45.6	22.3	6.6	3.3					

Table 16: Test set performance for Chinese-to-English controlled machine translation. Lower is better for ST-r and ST-s.

	BLEU	ROUGE-1	ROUGE-2	ROUGE-L	METEOR	ST-r	ST-s					
	Return-input baselines											
Syntactic input	6.2	29.9	9.2	34.4	13.2	13.9	0.0					
	Neural machine translation baselines											
OpenNMT	12.3	40.4	20.0	39.9	17.7	19.2	20.4					
Google Translate	30.3	63.2	37.7	56.6	32.0	18.5	21.3					
	Our work											
Zh-En	9.6	40.2	16.1	41.4	18.1	16.1	11.0					
Zh-En Big	11.9	44.3	19.1	44.5	20.4	15.7	10.0					

Table 17: Test set performance for English-to-Chinese controlled machine translation. Lower is better for ST-r and ST-s.

	En-En		n-En Fr-En		De-En		Es-En		Zh-En						
	sem.	syn.	Δ	sem.	syn.	Δ	sem.	syn.	Δ	sem.	syn.	Δ	sem.	syn.	Δ
Prior work	74.3	7.4	66.9	-	-	-	-	-	-	-	-		-	-	-
Our work	74.9	12.0	62.9	73.2	10.4	62.8	68.6	12.1	56.5	72.6	12.9	59.7	73.6	16.3	57.3

Table 18: Pearson's correlation (%) for the English semantic similarity task.

		Es-En		Zh-En				
	sem.	syn.	Δ	sem.	syn.	Δ		
Fasttext		48.0			74.0			
Our work	76.3	49.0	27.3	76.2	23.5	52.8		

Table 19: Pearson's correlation (%) for the Spanish semantic similarity and Chinese semantic similarity tasks.

	POS	S Accur	acy	CP Labeled F_1			
	sem.	syn.	Δ	sem.	syn.	Δ	
Oracle		62.3			71.1		
Random		12.9			19.2		
Prior work	20.3	43.7	23.4	24.8	40.9	16.1	
En-En	19.6	44.9	25.3	24.2	42.4	18.2	
Fr-En	19.9	41.8	21.9	24.2	41.8	17.6	
De-En	20.1	44.7	24.6	24.4	42.0	17.6	
Es-En	19.7	44.0	24.4	24.1	41.5	17.4	
Zh-En	19.7	44.4	24.7	24.4	41.7	17.3	

Table 20: POS tagging accuracy (%) and constituent parsing labeled F_1 scores (%) for the English syntactic evaluation. The models are trained on 5 million sentence pairs.

	PO	S Accur	acy	CP	Labeled	F_1		
	sem.	syn.	Δ	sem.	syn.	Δ		
Oracle Fr		71.7			92.8			
Random Fr		18.2			31.0			
fastText		28.5			34.7			
Fr-En	22.5	51.2	28.7	33.1	42.5	9.4		
Oracle De		67.7			99.9			
Random De		17.7		46.5				
fastText		27.0		51.7				
De-En	21.5	47.4	25.9	50.3	58.1	7.8		
Oracle Es		56.8			64.2			
Random Es		9.7			16.8			
fastText		21.7			23.2			
Es-En	13.7	34.9	21.2	19.0	34.0	15.0		
Oracle Zh		56.6			58.2			
Random Zh		13.4			17.8			
fastText		18.7			21.7			
Zh-En	15.0	36.2	21.2	19.3	32.3	12.9		

Table 21: POS tagging accuracy (%) and constituent parsing labeled F_1 scores (%) for the multilingual syntactic evaluation. The models are trained on 5 million sentence pairs.